


# HPoE switch 16 ports ZTP-ZP1016-HPoE



## Key Features

- Multiple working modes to address your business needs: Normal, Secure and Surveillance
- Support port traffic control
- Support for secure mode, all downlink ports can communicate only with uplink ports
- Up to 250m transmission distance on surveillance mode
- Support buffer optimization
- All metal housing, safe and reliable

## Specifications

Model	ZTP-ZP1016-HPoE
Ports	16×100Mbps PoE ports (RJ45)+2×1000Mbps Combo ports
Standards	IEEE802.3,IEEE802.3u,IEEE802.3z,IEEE802.3ab,IEEE802.3x,IEEE802.3af,IEEE802.3at,IEEE802.3az
Switching capacity	7.2Gbps
Forwarding performance	5.36Mpps
Packet Buffer	4M bit
MAC	16K
Dimensions (W×D×H)	440mm x 207mm x 45mm(17.3"×8.1"×1.8")
Weight	<4.2kg
Power supply	AC: 100-240V, 50/60Hz
PoE	802.3at/af
Max. PoE Power	Max capacity: 250W Max capacity for single port: 30W

Cooling Fans	2
Mean Time Between Failure (MTBF)	>50000 hours
Ambient temperature	0°C-45°C (32°F-113°F)
Operating humidity	10%~90% (noncondensing)
Storage humidity	5%~90% (noncondensing)
Indicator	PWR: Steady on: AC input is normal Off: No AC input
	PoE: Off: No PoE power supply Steady on: PoE power supply is normal Flashing: PoE power supply is abnormal
	LINK/ACT: Off: No link Steady: Linked at 10/100Mbps Flashing: Transmitting data
	Speed: Off: Linked at 10/100Mbps On: Linked at 1000Mbps
Working Mode	Default(Normal mode) : All ports can communicate with each other. VLAN(Secure mode): Downlink ports can communicate only with uplink ports. EXTEND(Surveillance mode): Transmission distance up to 250 meters.